

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

DATE OF PREP 6/5/1999 (Rev 8/5/99)

SECTION I

MANUFACTURERS NAME

UNIROOF INTERNATIONAL INC.

STREET ADDRESS

CITY, STATE, AND ZIP CODE

P.O.BOX 160003

ALTAMONTE SPRINGS, FL. 32716

EMERGENCY PHONE NO.

407-869-5255

PRODUCT CLASS

MANUFACTURERS CODE IDENTIFICATION

URETHANE ACRYLIC-LATEX EXTERIOR COATING

TRADE NAME

FORMFLEX 6000

6160

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	PPM	TLV		VAPOR PRESSURE
			mg/M3	LEL	
ETHYLENE GLYCOL CAS#'107-21-1	2.00%	50		3.2%	.10mmHg

SECTION III - PHYSICAL DATA

BOILING RANGE 379-401 VAPOR DENSITY [] HEAVIER, [] LIGHTER, THAN AIR

EVAPORATION RATE [] FASTER [] SLOWER, THAN ETHER ;

PERCENT VOLATILE 100.0%; WEIGHT PER GALLON-9.25#

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY na FLASH POINT 232 LEL

EXTINGUISHING MEDIA **CO2, FOAM, & DRY CHEMICAL**

UNUSUAL FIRE AND EXPLOSION HAZARDS **CLOSED CONTAINERS MAY EXPLODE WHEN**

EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC.

SPECIAL FIRE FIGHTING PROCEDURES WEAR SELF CONTAINED BREATHING APPARATUS.

WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE

STREAM WILL SPREAD FIRE.

FORMFLEX 6000 MSDS - PAGE 2

SECTION V- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE NONE ESTABLISHED

EFFECTS OF OVEREXPOSURE INHALATION OF VAPORS IN POORLY VENTILATED MAY CAUSE HEADACHE OR DIZZINESS. SKIN ABSORPTION SHOULD NOT BE A PROBLEM. DIRECT CONTACT MAY CAUSE EYE IRRITATION.

EMERGENCY FIRST AID PROCEDURE REMOVE TO FRESH AIR. WASH EXPOSED AREAS WITH SOAP AND WATER. FLUSH EYES WITH COPIOUS AMOUNTS OF WATER IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN.

SECTION VI - REACTIVITY DATA

STABILITY: () UNSTABLE (x) STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION () MAY OCCUR (x) WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: IF APPLIED BY SPRAYING, PARTICLE MASK SHOULD BE USED TO AVOID INHALATION OF ATOMIZED PAINT.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE EQUIPMENT: N/A

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL PLACE

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

AVOID CONTACT WITH SKIN OR CLOTHING.

KEEP CONTAINER CLOSED.

WASH THOROUGHLY AFTER USING.

Formflex 6000 6160 6/7/99