

155AF Amphibikote (wet and dry)

DESCRIPTION:

Karnak #155AF Amphibikote is a carefully prepared, emergency roof cement with special water displacing characteristics, which ensures an effective bond to both wet and dry surfaces. The ability to adhere during inclement weather conditions makes Karnak #155AF Amphibikote the first choice of both roofing contractors and plant engineers. Karnak #155AF Amphibikote is composed of selected asphalts, mineral fillers combined with refined solvent, and special chemical ingredients which give it a unique water displacement quality.

USES:

Karnak #155AF Amphibikote is a cold process, heavy bodied, trowel applied emergency roof cement ideal for repairing leaks in asphalt built-up roofs, flashing on walls, chimneys, skylights and vents, down-spouts and gutters. The dried film retains its flexibility and ductility so the coating will resist extreme variations in temperature and weather.

SPECIFICATIONS:

ASTM D-4586 Type I
ASTM D-3409

Federal Specification SS-C-153 Type I (except asbestos free)

SURFACE PREPARATION:

All surfaces should be clean and free from oil, grease, rust, dirt, and other foreign matter. Excess water should be removed if possible before application of Karnak #155AF Amphibikote.

APPLICATION:

Karnak #155AF Amphibikote is ready to use directly from the container. No heating is required. Spread Karnak #155AF Amphibikote by trowel to an average thickness of 1/8" (8 gals. per square per coat) or greater to all surfaces to be treated. To repair large cracks or breaks, spread Karnak #155AF Amphibikote over the damaged area, then embed Karnak Cotton, Glass or Poly-Mat membrane Reinforcement and re-apply another coat of Karnak #155AF Amphibikote over the entire patch.

CARE OF TOOLS:

Trowels and other equipment should be thoroughly cleaned with mineral spirits, taking necessary precautions when handling combustible materials.

CAUTION:**KARNAK**

Distributed by: **BEST MATERIALS LLC**
Ph: 800-474-7570, 602-272-8128
Email: sales@bestmaterials.com
www.bestmaterials.com

METRO-DADE
APPROVED

155AF Amphibikote (wet and dry)

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 5 gallon pails, 1 gallon cans and 10 oz. cartridges.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Distributed by: BEST MATERIALS LLC
Ph: 800-474-7570, 602-272-8128
Email: sales@bestmaterials.com
www.bestmaterials.com